

Apollo

USER MANUAL



Convenient filling with two adjustable holes at the bottom, no part to detach. Gold plated 510 connector pin.



Quartz glass and silicon ring provides heat and leak protection



510 Drip tip uses acrylic material to seal the heat. It stays cool after long vaping.



Drop Proof design



Anti-Leak design with Top vs Bottom adjustable airflow



Protective Silicon Sleeve. Atomizer body is not too hot when it comes into contact with skin.



Unique coil design with both regular and Ni200 temperature control coil

6ML Tank capacity



0.1ohm(Single)
rated at 300F-600F
Φ0.3mm
Spacing:1.5-2mm



0.3ohm(Single)
rated at 30-60W
Φ0.5mm
Spacing:1.5-2mm

Compatible MODS

- IPVD2
- IPV4
- Joyetech eVic VT
- SX MINI ML Class
- SMOK Xpro
- SMOK Cube II 160W

For other MOD, make sure the coil resistance is within the operating range of your MOD.

Package Contents

- 1*ZPAL Apollo Tank
- 1*0.3 ohm coil pre-installed
- 1*0.1 ohm Ni200 coil extra
- 1*Protective Silicon Sleeve
- 1*User Manual



USA Website: www.zpaltech.com
China Website: www.zpal.com.cn

Apollo

Specifications

Coil:	0.3 ohm (Single), 0.1 ohm (Ni200)
Wattage:	30-60watts(0.3ohm) 300F-600F(0.1ohm)
Airflow:	Dual Adjustable Airflow
Material:	304 Stainless Steel
Drip Tip:	Wide Bore
Cotton:	Organic
Glass Tube:	Quartz
Connection:	510 Stainless Steel
Capacity:	6ml
Size:	23X83mm
Weight:	100g

Important Safety Information

When you are using a fresh coil, make sure that you first saturate the coil with e-liquid before started to use it. If you do not take this step, the coil can burn or even catch on fire.

Do not let the tank become completely empty. Refill the tank to avoid dry burning or damage to the coil.



USA Website: www.zpaltech.com
China Website: www.zpal.com.cn


Apollo

First Time Use

1. With the mouthpiece downwards, unscrew by gripping the bottom collar (There is a vacuum seal so unscrewing can feel a little resistant at first).
2. Add a few drops of e-liquid inside the coil to soak the cotton wick. This will prevent dry burning the coil.
3. When done, carefully line up the screw threads and screw all the way back to create a proper seal.

Filling E-liquid

1. With the mouthpiece downwards, twist the bottom collar arrow and set it to e-liquid indicator.
2. Now both filling holes are open. You can aim the nozzle into the hole and gently push the e-liquid down to avoid spilling (Do not overfill the tank).
3. When done twist the bottom collar arrow and set it back to vaping indicator.
4. With tissue, wipe away any liquid spillages or residues and wash/dry hands thoroughly.
5. Wait at least 3 minutes for e-liquid to settle and absorb into cotton wick.
6. Attach to compatible mod.



USA Website: www.zpaltech.com
China Website: www.zpal.com.cn

WARNING



This product is not intended for use by persons under 18-year-old, women who are pregnant or breastfeeding, or persons with or at risk of heart disease, high blood pressure, diabetes, or taking medicine for depression or asthma. Our products do not treat, diagnose, or cure any disease, physical ailment, or condition. Keep out of the reach of children and pets as ingestion of certain pieces can present a choking hazard.

Apollo

Dismantle

1. First remove your tank from attached mod.
2. Carefully unscrew the base piece ensuring no pressure is applied to the glass tank during this process.
3. The glass tube can now be removed, this piece is a press fit so grip firmly and twist to remove. If you're struggling to get a firm grip a rubber band can come in handy.
4. At this point the drip tip can be removed from the top piece, this is really easy to do simply pull and it should come out. Be careful as it is held in place with a silicon o-ring which should be checked to ensure a tight fit between the top collar and drip tip installed.
5. The coil can now be removed, be careful if the unit has been used recently as there may still be some e-liquid left on this part!

Warranty


90 days (This warranty voids if this product is installed improperly or in an improper environment, overloaded, misused, opened, abused, or altered in any manner, or is not used under normal operating conditions or not in accordance with any label or instruction).




USA Website: www.zpaltech.com
China Website: www.zpal.com.cn

Apollo


Dismantle



Air intake slot



Coil Replacement



USA Website: www.zpaltech.com
China Website: www.zpal.com.cn