

HALO

USER MANUAL



Top filling with two filling holes make filling easy and convenient.



Quartz glass and silicon ring provides heat and leak protection.



510 Drip tip uses acrylic material to seal the heat. It stays cool after long vaping.



Dual adjustable airflow with two air inlets located at drip tip and atomizer base. Adjustable liquid flow to control how much juice going into the coil.



Unique DVC design delivers maximum flavor and vapor production.

3ML Tank capacity



0.5ohm 316L SS (dual vertical) (rated at 20-160W)

Package Contents

- 1*ZPAL Halo Tank
- 1*0.5ohm SS coil pre-installed
- 1*Glass extra
- 1*0.5ohm SS coil extra
- 1*User Manual



HALO

Specifications

- Coil: 0.5ohm 316L SS (20-160watts)
- Airflow: Dual Adjustable Airflow
- Material: 316L Stainless Steel
- Drip Tip: 510 Drip tip with Acrylic
- Cotton: Organic
- Glass Tube: Quartz
- Connection: 510 Stainless Steel
- Capacity: 3ml
- Size: 22X70mm
- Weight: 60g

First Time Use

1. Unscrew by gripping the bottom collar (There is a vacuum seal so unscrewing can feel a little resistant at first).
2. Add a few drops of e-liquid inside the coil to soak the cotton wick. This will prevent dry burning the coil.
3. When done, carefully line up the screw threads and screw all the way back to create a proper seal.

When vaping

- below 100W, you can completely close top adjustable airflow located around drip tip to get maximum e-liquid flavor
 - over 100W, you can slowly open top adjustable airflow to let fresh air in and mix with hot vapor
- It is recommended to gradually increase the wattage from low to high instead of jumping to high wattage right away.



HALO

Filling E-liquid

1. Pull the drip tip base out until it is completely detached.
2. Twist the bottom collar clockwise until coil chamber holes completely close.
3. Twist the top collar arrow counterclockwise and set it to e-liquid indicator. At this time top filling holes will open.
4. Aim the nozzle into one side hole (Do not overfill the tank)
5. Twist the top collar arrow clockwise and set it to vaping indicator. At this time top filling holes will close.
6. When done push the drip tip base all the way in.
7. Twist the bottom collar counterclockwise until coil chamber holes open.
8. With tissue, wipe away any liquid spillages or residues and wash/dry hands thoroughly.
9. Wait at least 3 minutes for the e-liquid to settle and absorb into cotton wick.



WARNING



This product is not intended for use by persons under 18-year-old, women who are pregnant or breastfeeding, or persons with or at risk of heart disease, high blood pressure, diabetes, or taking medicine for depression or asthma. Our products do not treat, diagnose, or cure any disease, physical ailment, or condition. Keep out of the reach of children and pets as ingestion of certain pieces can present a choking hazard.

HALO

Dismantle

1. First remove your tank from attached mod.
2. Carefully unscrew the base piece ensuring no pressure is applied to the glass tank during this process.
3. The glass tube can now be removed, this piece is a press fit so grip firmly and twist to remove. If you're struggling to get a firm grip a rubber band can come in handy.
4. At this point the drip tip can be removed from the top piece, this is really easy to do simply pull and it should come out. Be careful as it is held in place with a silicon o-ring which should be checked to ensure a tight fit between the top collar and drip tip installed.
5. The coil can now be removed, be careful if the unit has been used recently as there may still be some e-liquid left on this part.

Important Safety Information

- When you are using a fresh coil, make sure that you first saturate the coil with e-liquid before started to use it. If you do not take this step, the coil can burn or even catch on fire.
- Do not let the tank become completely empty. Refill the tank to avoid dry burning or damage to the coil.
- If you are not using the tank for couple days, you can close coil chamber holes to prevent leaks.



HALO

Dismantle



Air intake slot



Coil Replacement

